

Fluid & Air Transfer - Air Hose

Air Hose



MINE AIR/WATER HOSE

For mining, construction and industrial use where 400 PSI service is required. Mandrel built.

- Yellow cover - weather, cut & abrasion resistant synthetic rubber
- Smooth black, oil mist resistant, synthetic rubber tube
- Reinforced with multiple layers of high tensile, spiraled synthetic wound yarn
- Temperature range: -40°C to +82°C (-40°F to +180°F)
- Sizes: ½" - 4" I.D.
- Standard length - 50' (other lengths available)

Product Number	I.D. inches	O.D. inches	Max W.P. PSI	Approx Wt. Per ft. lbs.
46-050-050	0.5	0.95	400	0.31
46-075-050	0.75	1.26	400	0.41
46-100-050	1	1.54	400	0.61
46-125-050	1.25	1.89	400	0.81
46-150-050	1.5	2.12	400	0.91
46-200-050	2	2.63	400	1.2
46-300-050	3	3.7	400	2.37
46-400-050	4	4.8	400	3.3

WIRE REINFORCED AIR HOSE

- High pressure air service to mining, construction & industrial use
- Yellow cover with red stripe
- Cut & gouge resistant synthetic rubber
- Reinforced with layers of high tensile steel wire
- Temperature Range: -40°C to +85°C
- Sizes: ½" - 4" I.D..
- Standard length - 50' (other lengths available)

Product Number	I.D. inches	O.D. inches	Max W.P. PSI	Approx Wt. Per ft. lbs.
46-050-050WR	0.5	0.8	600	0.44
46-075-050WR	0.75	1.14	600	0.54
46-100-050WR	1	1.3	600	0.68
46-125-050WR	1.25	1.66	600	0.83
46-150-050WR	1.5	2.05	600	1.12
46-200-050WR	2	2.63	600	1.58
46-250-050WR	2.5	3.27	450	2.4
46-300-050WR	3	3.78	450	2.86
46-400-050WR	4	4.8	450	4.13

Air Hose Accessories

