# Blasting - Gauge & Strap

### Depth Gauge

Developed for seismographic measuring, these tough fiberglass tapes are used by a variety of industries to measure depth. Attach any weight to the snap ring and lower to measure depth. The depth gauges are incredibly durable, flexible and lightweight with graduations printed on both sides.

#### **FEATURES**

- Numbers are graduated from the weighted end of the tape strap.
- Tough, flexible and lightweight with graduations printed on both sides.
- White with black and red markings.
- Coating: Clear Coat.
- Tensile Strength: 100kg / 200 lbs.



#### Accessories

PART NUMBER	DESCRIPTION
47-3508	Lead weight, 8 OZ tear drop

## Strapping

- **Multiple Uses** Bundling, bailing, securing loads, anchoring, etc. Polywoven strapping can be used to replace steel and wire strapping in many applications.
- Safe Safe to vehicles, machinery and/or product. Safe to handle. No protective clothing necessary; no sharp edges or splinters. No potential hazards involving off-cuts. No danger of injury when cutting strapping under tension.
- Cost Efficient Requires no expensive machinery. Reusable, therefore reducing waste. Machinery repair costs eliminated. Save on labour.
- **Easy Handling** Light and easy to handle. Easily disposed.
- **Recovery** Elongation is approximately 8% and has a 90% recovery. Strapping expands and contracts while maintaining its tension on the bundle. If a bundle is dropped, the strapping will not break due to its flexibility.
- **Resistant to** Ultraviolet rays...Acids...High and low temperatures... Water...Rust—thereby leaving no marks on product.
- **Tensioning** Hand-held tool and wire buckles produce tensioning. Complete line of strapping tools for different requirements. Tool repair service available

Strapping				
Product Number	Size	Minimum Break Strength	Foot per Coil	
STR-40PBS	1/2"	660 lbs	1,500'	
10650	1/2"	1,047 lbs	1,500'	

	Buckles and Tools			
Product Number	Size	Description		
10001	1/2"	C4 Buckle (1000 bx) plain		
10310		Heavy duty tensioner for straps up to 1 1/2" (38 mm).		





